

Consultancy in Applied Research, Engineering and Development Ltd.
safety data sheet

pursuant to Regulation (EC) No 1907/2006

PLA-Y Glue

Revised on: 9.1.2025

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PLA-Y Glue

UFI: 1QY0-CCKR-Y503-W0NP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

Uses advised against

Any improper use.

1.3. Details of the supplier providing the safety data sheet

Company name: Consultancy in Applied Research, Engineering and Development Ltd. 24
Street: Marian Park, Baldoyle, Baldoyle
Location: IRL-D13P9Y1 Dublin
Phone: + 492216776677
E-mail: info@cared.ie

1.4. Emergency number: + 49 6195 8092523

More information

Safety data sheet according to Regulation (EC) No 1907/2006 (amended by Regulation (EU) No 2020/878)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard-determining components for labeling

Solvent A

Signal word:

Danger

Pictograms:



hazard warnings

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.

safety instructions

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.

Consultancy in Applied Research, Engineering and Development Ltd.
safety data sheet

pursuant to Regulation (EC) No 1907/2006

PLA-Y Glue

Revised on: 9.1.2025

Page 2 of 13

P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/national/international regulations.

Special labelling of certain mixtures

For commercial use only.

2.3. Other hazards

In use, formation of explosive/highly flammable vapour/air mixtures is possible. The substances in the mixture (>0.1%) do not meet the PBT/vPvB criteria according to REACH, Annex XIII This product does not contain any substance (>0.1%) that exhibits endocrine properties towards humans, as none of the ingredients meet the criteria. This product does not contain any substance (>0.1%) that exhibits endocrine properties towards non-target organisms, as none of the ingredients meet the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Dangerous ingredients

CAS No.	substance name			Portion
	EC No.	index number	REACH No.	
	Classification (Regulation (EC) No 1272/2008)			
000-00-0	Solvent A			90 - < 99 %
	000-000	000-000-00		
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H- and EUH-phrases: see section 16. **Specific**

concentration limits, M-factors and ATE

CAS No.	EC No.	substance name	Portion
		Specific concentration limits, M-factors and ATE	
000-00-0	000-000	Solvent A	90 - < 99 %
	inhalation: LC50 = 68.4 mg/l (vapors); dermal: LD50 = 9040 mg/kg; oral: LD50 = > 2000 mg/kg		

More information

The product does not contain any listed SVHC substances > 0.1% according to Regulation (EC) No. 1907/2006 § 59 (REACH).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or if you feel unwell, seek medical attention immediately (if possible, show the operating instructions or safety data sheet). Remove soiled, soaked clothing immediately. First aider: Pay attention to self-protection!

After inhalation

Remove the person to fresh air and ensure comfortable breathing. If irritation of the respiratory tract occurs, seek medical attention.

After skin contact

Remove contaminated clothing immediately. Wash with plenty of water. If skin irritation occurs, seek medical attention.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses if possible. Continue rinsing. If eye irritation persists: Get medical advice/attention.

PLA-Y Glue

Revised on: 9.1.2025

Page 3 of 13

After ingestion

Rinse mouth thoroughly with water. Have patient drink plenty of water in small sips (dilution effect). DO NOT induce vomiting. Never give anything by mouth to an unconscious person or to someone who is having convulsions. If symptoms occur or in all cases of doubt, seek medical advice.

4.2. Most important acute and delayed symptoms and effects

See sections 2 and 11

4.3. Indication of any immediate medical attention or special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing agents

Suitable extinguishing agents

Carbon dioxide (CO₂). Dry extinguishing agent. Alcohol-resistant foam. In case of major fires and large quantities: water spray.

Unsuitable extinguishing agents

full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire the following may be released: Gases/vapours, irritant. Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Instructions for firefighters

In case of fire: Use self-contained breathing apparatus. Do not breathe explosion or fire gases. Flashback possible at great distances.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow to enter drains or waterways. Use a water spray jet to protect people and to cool containers in the danger area. In the event of a major fire and large quantities: evacuate the area. Fight the fire from a distance due to the risk of explosion.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General information

Ventilate the affected area. Do not breathe gas/fumes/vapours/spray. Avoid contact with skin, eyes and clothing.

Personnel not trained for emergencies

Remove persons to safety. Remove all sources of ignition. Ventilate the affected area. Wear personal protective equipment. (See section 8.)

emergency services

Use a self-contained breathing apparatus whenever there is a possibility of uncontrolled release, the extent of exposure is unknown, or in situations where air-filtering respirators do not provide adequate protection.

6.2. Environmental protection measures

Do not allow to enter drains or waterways. Danger of explosion! Cover drains. Prevent spread over a large area (e.g. by damming or using oil barriers). Inform the relevant authorities if gas escapes or enters waterways, soil or drains.

6.3. Methods and materials for containment and cleaning

For restraint

Absorb with liquid-binding material (sand, diatomaceous earth, acid binders, universal binders).
Ventilate the affected area.
Treat recovered material according to the Disposal section.

PLA-Y Glue

Revised on: 9.1.2025

Page 4 of 13

For cleaning

Clean contaminated objects and surfaces thoroughly, observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7 Personal protective
equipment: see section 8 Disposal: see section
13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Instructions for safe handling

Ensure adequate ventilation and local exhaust ventilation at critical points. Do not breathe gas/vapour/spray. Avoid contact with skin, eyes and clothing. Wear suitable protective clothing when working. (See section 8.)

Information on fire and explosion protection

Keep away from sources of ignition - do not smoke. Take measures against electrostatic charges. Flammable vapors can accumulate in the vapor space of closed systems. During use, explosive/highly flammable vapor/air mixtures may form. Heating leads to an increase in pressure and the risk of bursting.

Information on general hygiene measures in the workplace

The usual precautions when handling chemicals must be observed. Keep away from food, drink and animal feedingstuffs.
Always close containers tightly after removing the product. Do not eat, drink or smoke while working. Wash hands before breaks and at the end of work. Preventive skin protection with skin protection cream. Remove contaminated clothing and wash it before wearing it again.

Further information on handling

Protective and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and containers

Keep container tightly closed and store in a cool, well-ventilated place. Protect from direct sunlight.

Ensure adequate ventilation of the storage room.

Ensure that leaks can be collected (e.g. drip trays or collecting areas).

storage instructions

Do not store together with: Gas. Explosives. Flammable solids. Self-igniting (pyrophoric) liquids and solids. Self-heating substances or mixtures. Substances and mixtures which emit flammable gases in contact with water. Oxidizing liquids. Oxidizing solids. Ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-flammable toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packaging dry and tightly closed to avoid contamination and absorption of moisture.

Protect against: UV radiation/sunlight. Heat. Humidity. Frost. Storage
temperature: 15 - 25°C

Storage class according to TRGS 510: 3 (Flammable liquids)

7.3. Specific end uses

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Parameters to be monitored

Consultancy in Applied Research, Engineering and Development Ltd.
safety data sheet

pursuant to Regulation (EC) No 1907/2006

PLA-Y Glue

Revised on: 9.1.2025

Page 5 of 13

occupational exposure limits

CAS No.	Designation	ppm	mg/m ³	F/m ³	top-limiting factor	Art
000-00-0	Solvent A	50	150		2(II)	TRGS 900

DNEL/DMEL values

CAS No.	Designation			
DNEL type	route of exposure	Effect	Value	
000-00-0	Solvent A			
Employee DNEL, long-term	inhalation	systemic	3.306 mg/m ³	
Employee DNEL, long-term	dermal	systemic	1.18 mg/kg body weight/day	

PNEC values

CAS No.	Designation		
environmental compartment		Value	
000-00-0	Solvent A		
Freshwater		19.7 mg/l	
freshwater (intermittent release)		0.95 mg/l	
seawater		1.97 mg/l	
freshwater sediment		77.7 mg/kg	
marine sediment		7.77 mg/kg	
microorganisms in sewage treatment plants		1 mg/l	
Floor		2.62 mg/kg	

8.2. Limitation and monitoring of exposure



Suitable technical control devices

Technical measures and the application of appropriate work procedures take priority over the use of personal protective equipment.

Ensure adequate ventilation and local exhaust ventilation at critical points. Process in closed systems.

Individual protective measures, such as personal protective equipment

eye/face protection

Recommended eye protection products: Tightly fitting safety goggles. (DIN EN 166)

hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable protective gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0.5 mm

Breakthrough time: ≥ 480 min. Penetration time (maximum wearing time): ~ 120 min. (estimated) For special applications, it is recommended to check the chemical resistance of the protective gloves mentioned above with the glove manufacturer.

The gloves to be used must meet the specifications of EC Regulation (EU) 2016/425 and the resulting standard EN ISO 374.

Check for leaks/impermeability before use. If gloves are to be reused, clean them before removing them and store in a well-ventilated place.

PLA-Y Glue

Revised on: 9.1.2025

Page 6 of 13

body armor

Wear flame-retardant clothing. Minimum protective measures according to TRGS 500.

respiratory protection

When used correctly and under normal conditions, respiratory protection is not required. Respiratory protection is required for:

Exceeding limit Release
of: Product. Insufficient
ventilation

Suitable respiratory protection device: Combination filter device (EN 14387) Filter type: A/P3

The respiratory protection filter class must be adapted to the maximum pollutant concentration (gas/vapor/aerosol/ particles) that can arise when handling the product. If the concentration is exceeded, an isolation device must be used! The wearing time limits according to the GefStoffV in conjunction with the rules for the use of respiratory protection devices (DGUV Rule 112-190) must be observed.

Limiting and monitoring environmental exposure

Do not allow the product to enter the environment in an uncontrolled manner.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

state of aggregation:	fluid	
Color:	transparent	
Odor:	characteristic	
Odor threshold:	not determined	
Melting point/freezing point: Boiling point or initial boiling point and boiling range:		not determined not determined
Flammability:		not determined
Lower explosion limit:		not determined
Upper explosion limit:		not determined
Flash point:		- 3 (Solvent A) °C not determined
Ignition temperature:		
Decomposition temperature:		not relevant
PH value:		7.0
Kinematic viscosity:		not determined
Water solubility:		not determined
solubility in other solvents		
not determined		
dissolution rate:		not relevant
distribution coefficient n-octanol/water:	SECTION 12: Ecological information	
Dispersion stability:		not relevant
vapor pressure:		not determined
Density:		not determined
Bulk density:		not relevant
Relative vapor density:		not determined
Particle properties:		not relevant

9.2. Other information

information on physical hazard classes

explosion hazards

In use, formation of explosive/highly flammable vapour/air mixtures is possible. Auto-ignition temperature

Gas: not determined

PLA-Y Glue

Revised on: 9.1.2025

Page 7 of 13

Oxidizing properties
none.

Other safety-related parameters

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined
Solid content:	not determined
Sublimation temperature:	not relevant
Softening point:	not relevant
Pour point:	not relevant
Dynamic viscosity:	not determined
run-out time:	not determined

More information

No information is available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information is available.

10.2. Chemical stability

The mixture is chemically stable under recommended storage, use and temperature conditions.

10.3. Possibility of hazardous reactions

If handled and stored as directed, no dangerous reactions will occur. See chapter 10.5.

10.4. Conditions to avoid

Protect from heat. Danger of explosion!
May form explosive/flammable vapour/air mixtures when used. Heating will increase pressure and cause explosion hazard.

10.5. Incompatible materials

Substances to avoid: Strong oxidizing agents. Strong reducing agents. Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Does not decompose when used as intended.

SECTION 11: Toxicological information

11.1. Information on hazard classes within the meaning of Regulation (EC) No 1272/2008

Toxicokinetics, Metabolism and Distribution

No data available.

Acute toxicity

Based on the available data, the classification criteria are not met.

ATEmix calculates

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapor) > 20 mg/l; ATE (inhalative dust/mist) > 5 mg/l

CAS No.	Designation				
	route of exposure	dose	species	source	method
000-00-0	Solvent A				
	orally	LD50 > 2000 mg/kg	rat	REACH Dossier	OECD 401

Consultancy in Applied Research, Engineering and Development Ltd.
safety data sheet

pursuant to Regulation (EC) No 1907/2006

PLA-Y Glue

Revised on: 9.1.2025

Page 8 of 13

	dermal	LD50 mg/kg	9040	rabbit		
	inhalation (4 h) steam	LC50	68.4 mg/l	rat	REACH Dossier	OECD 403

irritant and corrosive effects

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

Based on the available data, the classification criteria are not met.

Carcinogenic, mutagenic and reproductive toxic effects

May damage fertility or the unborn child. (Solvent A) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Solvent A (CAS No.: 000-00-0):

In vitro mutagenicity:

Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay), OECD Guideline 476 (In Vitro Mammalian Cell Gene Mutation Test); Result: negative. Literature reference: REACH Dossier

Reproductive toxicity: Species: Rat; Method: OECD Guideline 415 (One-Generation Reproduction Toxicity Study); Result: NOAEC > = 125 ppm; Literature reference: REACH Dossier

Developmental toxicity/teratogenicity: Species: Rat; Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Result: NOAEL = 500 mg/kg; Literature reference: REACH Dossier

Specific target organ toxicity after single exposure

Based on the available data, the classification criteria are not met.

Specific target organ toxicity with repeated exposure

Based on available data, the classification criteria are not met. Solvent A (CAS No.: 000-00-0):

Subacute oral toxicity: Method: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents);

Exposure duration: 28 d. Species: Rat; Result: NOAEL = 298 ppm (135-205 mg/kg); Literature reference:

REACH Dossier; Hydrogen chloride gas. Subchronic inhalation toxicity: Method OECD Guideline 413

(Subchronic Inhalation Toxicity: 90-day Study); Species: Rat Exposure duration: 90 d. Result: NOAEC = 20 ppm. Literature reference: REACH Dossier

risk of aspiration

Based on the available data, the classification criteria are not met.

Specific effects in animal experiments

No data available.

11.2. Information on other hazards

endocrine disrupting properties

This product does not contain any substance (> 0.1%) that has endocrine disrupting properties in humans, as no ingredient meets the criteria.

Other Information

No data available.

SECTION 12: Ecological information

12.1. Toxicity

Based on the available data, the classification criteria are not met.

CAS No.	Designation					
	Aquatic toxicity	dose	[h] [d]	species	source	method
000-00-0	Solvent A					
	Acute fish toxicity	LC50 mg/l	> 95.4	96 h	Lepomis macrochirus	REACH Dossier OECD 203

Consultancy in Applied Research, Engineering and Development Ltd.
safety data sheet

pursuant to Regulation (EC) No 1907/2006

PLA-Y Glue

Revised on: 9.1.2025

Page 9 of 13

	Acute algae toxicity	ErC50 mg/l	> 877	72 hours	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EC50 mg/l	> 772	48 hours	Daphnia magna	REACH Dossier	OECD 202
	fish toxicity	NOEC mg/l	546.3	30 days	No data.	REACH Dossier	QSAR
	Acute bacterial toxicity	EC50 mg/l ()	> 100	3 hours	activated sludge of a predominantly domestic sewage	REACH Dossier	OECD 209

12.2. Persistence and degradability

CAS No.	Designation			
	method	Value	d	source
	Evaluation			
000-00-0	Solvent A			
	OECD 301 D	3.7	35	REACH Dossier
	Not readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

partition coefficient n-octanol/water

CAS No.	Designation	Log Pow
000-00-0	Solvent A	- 0.725

12.4. Mobility in soil

No data available.

12.5. Results of the PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, Annex XIII. The above statement applies to the substances contained in the product at a concentration of 0.1% or more.

12.6. Endocrine disrupting properties

This product does not contain any substance that exhibits endocrine disrupting properties towards non-target organisms as no ingredient meets the criteria.

The above statement applies to the substances contained in the product from 0.1%.

12.7. Other adverse effects

No data available.

Further information

Do not allow to enter drains or waterways.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

recommendations for disposal

Disposal in accordance with official regulations. Contact the responsible licensed waste disposal company for waste disposal. Non-contaminated and completely emptied packaging can be recycled. The allocation of waste key numbers/waste designations must be carried out in accordance with the EAKV, specific to the industry and process.

Suggested list of waste codes/waste designations according to EAKV/AVV:

Waste code - unused product

160305 WASTES NOT LISTED ELSEWHERE IN THE LIST; faulty batches and unused products; organic waste containing dangerous substances; hazardous waste

Waste code - used product

160305 WASTES NOT LISTED ELSEWHERE IN THE LIST; faulty batches and unused products; organic waste containing dangerous substances; hazardous waste

PLA-Y Glue

Revised on: 9.1.2025

Page 10 of 13

Waste code - uncleaned packaging

150110 PACKAGING WASTE, ABSORBENT MATERIALS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING (NEWS); packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances; hazardous waste

Disposal of uncleaned packaging and recommended cleaning agents

Contaminated packaging must be treated like the substance.

SECTION 14: Transport information

land transport (ADR/RID)

14.1. UN number or ID number: UN 1166
14.2. Proper UN shipping name: SOLVENT A
14.3. Transport hazard classes: 3
14.4. Packing group: II
Danger label: 3



Classification code: F1
Limited Quantity (LQ): 1 L
Exempted quantity: E2
transport category: 2
Hazard number: 33
Tunnel restriction code: D/E

inland waterway transport (ADN)

14.1. UN number or ID number: UN 1166
14.2. Proper UN shipping name: SOLVENT A
14.3. Transport hazard classes: 3
14.4. Packing group: II
Danger label: 3



Classification code: F1
Limited Quantity (LQ): 1 L
Exempted quantity: E2

maritime transport (IMDG)

14.1. UN number or ID number: UN 1166
14.2. Proper UN shipping name: SOLVENT A
14.3. Transport hazard classes: 3
14.4. Packing group: II
Danger label: 3



Marine pollutant: NO
Special provisions: -

PLA-Y Glue

Revised on: 9.1.2025

Page 11 of 13

Limited Quantity (LQ): 1 L
Exempted quantity: E2
EmS: FE, SD

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1166
14.2. Proper UN shipping name: SOLVENTA
14.3. Transport hazard classes: 3
14.4. Packing group: II
Danger label: 3



Limited Quantity (LQ) Passenger: 1 L
Passenger LQ: Y341
Exempted quantity: E2
IATA packing instructions - Passenger: IATA 353
maximum quantity - Passenger: IATA 5 L
packing instructions - Cargo: IATA 364
maximum quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for the user

See section 8.

14.7. Bulk cargo transport by sea according to IMO instruments

not relevant.

SECTION 15: Legal provisions

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Restrictions on use (REACH, Annex XVII):

Entry 3, Entry 40

Directive 2010/75/EU on industrial emissions: 94.67%

Directive 2004/42/EC on VOCs from paints and varnishes: 94.67%

Information on the SEVESO III Directive 2012/18/EU: P5c FLAMMABLE LIQUIDS

Additional information

Safety data sheet according to Regulation (EC) No 1907/2006 (amended by Regulation (EU) No 2020/878) The mixture is classified as hazardous according to Regulation (EC) No 1272/2008 [CLP].
REACH 1907/2006 Annex XVII, No. (Mixture): 3, 40

National regulations

Employment restriction: Observe employment restrictions for young people (Section 22 ArbSchG).
Observe employment restrictions for expectant and breastfeeding mothers (Sections 11 and 12 MuSchG).

Technical Instructions Air I: 5.2.5: Organic substances, expressed as total carbon at m >= 0.50 kg/h: Conc. 50 mg/m³

Portion:

PLA-Y Glue

Revised on: 9.1.2025

Page 12 of 13

Water hazard class: 1 - slightly hazardous to water
Status: Classification of mixtures according to Annex 1, No. 5 AwSV

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture have not been carried out.

SECTION 16: Other information

changes

Rev. 1.0; New creation: January 9, 2025

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
(Agreement concerning the International Carriage of Dangerous Goods by Road)
AwSV: Ordinance on Facilities for Handling Water-Hazardous Substances
AWV: Waste Catalogue Ordinance
CAS: Chemical Abstracts Service
CLP: Classification, Labeling and Packaging of substances and mixtures
DNEL: Derived No Effect Level
d: day(s)
EAKV: European Waste Catalogue according to the draft Waste Catalogue Regulation
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
ECHA: European Chemicals Agency
EWC: European Waste Catalog
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labeling of Chemicals
GefStoffV: Ordinance on Hazardous Substances, Germany)
h: hour
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect concentration
NLP: No-Longer Polymers

N/A: not applicable
OECD: Organization for Economic Co-operation and Development
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
(Regulations Concerning the International Transport of Dangerous Goods by Rail)
REACH: Registration, Evaluation, Authorization of Chemicals
SVHC: substance of very high concern
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
VOC: Volatile Organic Compounds
VwVwS: Administrative regulation on water-polluting substances
WGK: Water hazard class
Flam. Liq: Flammable liquids
Eye Irrit: Eye irritation
Repr: reproductive toxicity

Consultancy in Applied Research, Engineering and Development Ltd.
safety data sheet

pursuant to Regulation (EC) No 1907/2006

PLA-Y Glue

Revised on: 9.1.2025

Page 13 of 13

Classification of mixtures and evaluation method used according to Regulation (EC) No 1272/2008

[CLP]

classification	classification procedure
Flam. Liq. 2; H225	Based on test data
Eye Irrit. 2; H319	calculation method

Text of H- and EUH-phrases (number and full text)

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.

More information

The information in this safety data sheet corresponds to the best of our knowledge at the time of printing. The information is intended to give you guidance on the safe handling of the product named in this safety data sheet during storage, processing, transport and disposal. The information is not transferable to other products. If the product is mixed, blended or processed with other materials, or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material thus manufactured, unless expressly stated otherwise.

(The data of the relevant components were taken from the latest safety data sheet of the supplier taken.)